


| SAIPEM LTD | | | | | | COMPANY ACCEPTANCE OF FINAL VERSION | | |
|---|---------------------------------------|-----------------------------------|------------------------|---------------------------------|-----------------|--|---|----------|
| Revision | Date | Reason for issue | Prepared by | Checked by | Accepted by | <i>(stamp, signature)</i> | | |
| 1 | 2022.09.08 | Issued for Information | Christopher TAIT | Ian McARTHUR | Hugh THOMAS | | | |
| Document Title: | | | | | | Responsible Party | | |
| ENVIRONMENTAL REPORTING: PHYSICAL LOSSES AND PHYSICAL DISTURBANCES OF THE SEABED – DENMARK | | | | | | Contractor | | |
|  <p>SAIPEM Ltd.</p> <p>Saipem House - 12-42, Wood Street Kingston-upon-Thames Surrey KT1 1TG - United Kingdom</p> | | | | | | Page No. | | |
| | | | | | | 40 | | |
| | | | | | | Company acceptance code | | |
| | | | | | | <input type="checkbox"/> | 1 – Accepted without comments | |
| | | | | | | <input type="checkbox"/> | 2 – Accepted with comments to be incorporated | |
| <input type="checkbox"/> | 3 – Not accepted, revise and resubmit | | | | | | | |
| <input type="checkbox"/> | 4 – Issued for information | | | | | | | |
| TAG No. | | Language | | External Document Number | | | | |
| N/A | | English | | N/A | | | | |
| Registration codes | | | Document Number | | | | | |
| Contract No. | Work package | Project No. | Contractor | Area No. | Discipline Code | Document Type Code | Sequence | Language |
| 1000035546 | PER | PL1 | SAI | 12 | Z02 | RA | 00003 | EN |
| Area No. | Area Description | PL1-SAI-12-Z02-RA-00003-EN | | | | | | |
| 12 | OFFSHORE DK | | | | | | | |

Disclaimer: The sole responsibility of the publication lies with the author.
The European Union is not responsible for any use that may be made of information contained herein.

1. GENERAL INFORMATION

1.1. REVISION LOG TABLE

| Revision | Date | Changes from previous revision | Prepared by | Checked by | Accepted by |
|----------|------------|--------------------------------|------------------|--------------|-------------|
| 0 | 2022.08.04 | Issued for Information | Christopher TAIT | Ian McARTHUR | Hugh THOMAS |
| 1 | 2022.09.08 | Issued for Information | Christopher TAIT | Ian McARTHUR | Hugh THOMAS |

1.2. HOLD RECORD TABLE

| Hold No. | Section | Description of Hold |
|----------|---------|---------------------|
| 1. | | |

1.3. ABBREVIATIONS TABLE

| Abbreviation | Definition |
|--------------|---|
| BPP | Baltic Pipe Project |
| DPFPV | Dynamically Positioned Fall Pipe Vessel |
| EU | European Union |
| KP | Kilometre Post |
| PCI | Projects of Common Interest |
| SSDV | Side Stone Dumping Vessel |
| UXO | Unexploded Ordnance |

1.4. DEFINITIONS

For the purpose of the Procedure the following terms shall have the following meaning:

- a) **Company** means Gaz-System S.A.
- b) **Contract** means a written agreement between Company and Contractor.
- c) **Contractor** means Saipem Ltd., including their Subcontractors.
- d) **Project** Baltic Pipe Project
- e) **Subcontractor** means any entity contracted by Saipem Ltd. to undertake the Work for the Baltic Pipe Project.

1.5. REFERENCE DOCUMENT SECTIONS

| Ref. | Document Number | Rev. | Document Title |
|--------------------------------|----------------------------|------|---|
| Company Documents | | | |
| /1/ | - | - | Permit for Baltic Pipe Natural Gas Pipeline in the Baltic Sea |
| /2/ | PL1-RAM-12-Z02-RA-00003-EN | - | Environmental Impact Assessment – Baltic Sea – Denmark |
| /3/ | PL1-RAM-10-Y01-XD-00001-EN | 7M | Alignment Sheets |
| Contractor Documents | | | |
| /4/ | PL1-SAI-00-S00-KA-00008-EN | 3 | Environmental Monitoring Programme – Denmark (Offshore) |
| Subcontractor Documents | | | |
| /5/ | PL1-SAI-12-J00-XF-42131-EN | - | Rohde Nielsen – Post Backfill Survey Charts (Denmark) – Area 1 |
| /6/ | PL1-SAI-12-J00-XF-42141-EN | - | Rohde Nielsen – Post Backfill Survey Charts (Denmark) – Area 2 |
| /7/ | PL1-SAI-12-J00-XF-42151-EN | - | Rohde Nielsen – Post Backfill Survey Charts (Denmark) – Area 3 |
| /8/ | PL1-SAI-12-Y03-XE-48013-EN | - | DEME – As-Built Drawing Danish Landfall Rock Placement |
| /9/ | PL1-SAI-12-Y03-XE-48016-EN | - | DEME – As-Built Drawing Lock Berm KP26.781 – Post-Lay |
| /10/ | PL1-SAI-12-Y03-XE-48005-EN | - | DEME – As-Built Drawing Lock Berm KP27.000 – Post-Lay |
| /11/ | PL1-SAI-12-Y03-XE-48006-EN | - | DEME – As-Built Drawing Kriegers Flak EC Crossing – Post-Lay |
| /12/ | PL1-SAI-12-Y03-XE-48007-EN | - | DEME – As-Built Drawing Lock Berm KP32.325 – Post-Lay |
| /13/ | PL1-SAI-12-Y03-XE-48008-EN | - | DEME – As-Built Drawing C-Lion Crossing – Post-Lay |
| /14/ | PL1-SAI-12-Y03-XE-48017-EN | - | DEME – As-Built Drawing Span Support KP164.026 – KP164.036 |
| /15/ | PL1-SAI-12-Y03-XE-48018-EN | - | DEME – As-Built Drawing Span Support KP164.071 – KP164.081 |
| /16/ | PL1-SAI-12-Y03-XE-48019-EN | - | DEME – As-Built Drawing Span Support KP164.891 – KP164.901 |
| /17/ | PL1-SAI-12-Y03-XE-48020-EN | - | DEME – As-Built Drawing Span Support KP164.928 – KP164.938 |
| /18/ | PL1-SAI-12-Y03-XE-48021-EN | - | DEME – As-Built Drawing Span Support KP165.130 – KP165.150 |
| /19/ | PL1-SAI-12-Y03-XE-48022-EN | - | DEME – As-Built Drawing Span Support KP166.102 – KP166.112 |
| /20/ | PL1-SAI-12-Y03-XE-48023-EN | - | DEME – As-Built Drawing Span Support KP167.015 – KP167.025 |
| /21/ | PL1-SAI-12-Y03-XE-48024-EN | - | DEME – As-Built Drawing Span Support KP167.042 – KP167.070 |
| /22/ | PL1-SAI-12-Y03-XE-48003-EN | - | DEME – As-Built Drawing – Post-Lay Rock Placement – Ronne Bank Stability Berm |
| /23/ | PL1-SAI-12-Y03-XE-48004-EN | - | DEME – As-Built Drawing Span Support KP178.333 – Post-Lay |

| Ref. | Document Number | Rev. | Document Title |
|------|----------------------------|------|---|
| /24/ | PL1-SAI-12-Y03-XE-48009-EN | - | DEME – As-Built Drawing Baltica Segment 3 Crossing – Post-Lay |
| /25/ | PL1-SAI-12-Y03-XE-48010-EN | - | DEME – As-Built Drawing Nord Stream 1A Crossing – Post-Lay |
| /26/ | PL1-SAI-12-Y03-XE-48011-EN | - | DEME – As-Built Drawing Nord Stream 1B Crossing – Post-Lay |
| /27/ | PL1-SAI-12-Y03-XE-48012-EN | - | DEME – As-Built Drawing Nord Stream 2 Crossing – Post-Lay |
| /28/ | PL1-SAI-12-J00-RA-43002-EN | - | Rohde Nielsen – Environmental Reporting: Restoration of the Seabed at Micro-Tunnel Exit – Denmark |

Table of Contents

| | |
|---|-----------|
| 1. GENERAL INFORMATION..... | 2 |
| 1.1. Revision Log Table..... | 2 |
| 1.2. Hold Record Table..... | 2 |
| 1.3. Abbreviations Table..... | 2 |
| 1.4. Definitions..... | 2 |
| 1.5. Reference Document Sections..... | 3 |
| 2. INTRODUCTION..... | 6 |
| 2.1. Project Description..... | 6 |
| 2.2. Purpose of Document..... | 7 |
| 3. Summary of Offshore Construction Activities..... | 8 |
| 3.1. Pipeline Route and KP Definition..... | 8 |
| 3.2. Seabed Intervention..... | 8 |
| 3.2.1. Spoil Storage Philosophy..... | 9 |
| 3.3. Pipeline Configuration Along Route..... | 10 |
| 3.4. Pipeline Start-Up and Anchor Handling Operations..... | 12 |
| 4. ENVIRONMENTAL REPORTING: PHYSICAL LOSSES AND PHYSICAL DISTURBANCES OF THE SEABED..... | 13 |
| 4.1. Seabed Topography..... | 13 |
| 4.1.1. Methodology..... | 13 |
| 4.1.2. Assessment..... | 15 |
| 4.2. Seabed Habitat Type..... | 32 |
| 4.2.1. Methodology..... | 32 |
| 4.2.2. Assessment..... | 36 |
| 4.3. Comparison with Predictions in Environmental Impact Assessment..... | 39 |

2. INTRODUCTION

2.1. PROJECT DESCRIPTION

The Baltic Pipe Project is being developed by both GAZ-SYSTEM S.A. and Energinet.dk as co-investors. The 36" Baltic Pipe offshore pipeline was installed between the east coast of Denmark and the northern coast of Poland with first gas scheduled to flow from Denmark to Poland in October 2022.

Baltic Pipe is recognised as an EU PCI project, with the purpose of the project being to further strengthen the European internal energy market by reaching the EU's energy policy objectives of affordable, secure and sustainable energy.

The Baltic Pipe Project involves the construction of a new bi-directional gas pipeline system that will connect the existing gas transmission systems of Denmark and Poland and for the first time enable shippers to flow gas directly from Norway to the markets in Denmark, Poland and their neighbouring markets. Baltic Pipe will also allow shippers to flow gas from Poland to the Danish and Swedish markets.

The Baltic Pipe project includes five major components:

1. Tie-in to the Norwegian offshore gas fields and pipeline back to Danish onshore gas transmission system;
2. Investments in strengthening of the Danish onshore gas transmission system for transit of gas to Poland;
3. A new compressor station on the east coast of Denmark;
4. Offshore pipeline linking east coast of Denmark and northern coastline of Poland which allows bi-directional gas transmission;
5. Investment in strengthening of the existing onshore Polish gas transmission system to receive gas from Denmark.

Energinet is responsible for the delivery of Item 1 to 3, while Gaz-System is responsible for Items 4 and 5. This document relates to the delivery of Item 4, the offshore pipeline between the east coast of Denmark and the northern coast of Poland.

A schematic of the five major components of the Baltic Pipe project is presented in Figure 2-1 below. The solid dark line indicates the Baltic Pipe offshore pipeline.




Figure 2-1: Baltic Pipe Overview

2.2. PURPOSE OF DOCUMENT

Saipem Ltd. previously prepared a document with title *Environmental Monitoring Programme – Denmark (Offshore)* [Ref. /4/], which was approved by the Danish Energy Agency, to satisfy Condition 14 of *Permit for Baltic Pipe Natural Gas Pipeline in the Baltic Sea* [Ref. /1/].

Section 4.2.2 of the aforementioned document describes the planned monitoring activities in relation to physical losses and physical disturbances of the seabed and outlines the reporting to be submitted to the Danish Energy Agency upon completion of the works.

The purpose of this document is to present the monitoring results to the Danish Energy Agency.

3. SUMMARY OF OFFSHORE CONSTRUCTION ACTIVITIES

3.1. PIPELINE ROUTE AND KP DEFINITION

Key locations along the pipeline route in Denmark are provided in Table 3-1. These locations are referenced relative to the pipeline Kilometre Post (KP) distance stated in the Alignment Sheets [Ref. /3/], where KP0.000 refers to the first dry weld on the Danish landfall site and KP273.947 refers to the first dry weld on the Polish landfall site.

Table 3-1: Key Locations on Pipeline Route – Denmark

| Location | Position | WGS 84 | |
|--|----------|----------------|----------------|
| | | Latitude – N | Longitude – E |
| First Dry Weld – Denmark Landfall Site | 0.000 | 55° 11' 18.64" | 12° 07' 11.76" |
| Micro-Tunnel Exit | 1.005 | 55° 11' 13.21" | 12° 08' 07.77" |
| Danish Territorial Waters Boundary | 38.106 | 55° 11' 13.24" | 12° 08' 07.49" |
| Danish EEZ Boundary | 47.111 | 55° 08' 35.48" | 12° 51' 09.27" |
| Danish EEZ Boundary | 132.102 | 55° 06' 19.35" | 14° 10' 55.64" |
| Danish Territorial Waters Boundary | 141.862 | 55° 06' 00.10" | 14° 20' 01.26" |
| Danish Territorial Waters Boundary | 192.175 | 54° 48' 42.95" | 14° 51' 13.13" |
| Danish EEZ Boundary | 217.806 | 54° 35' 02.41" | 14° 51' 33.04" |

3.2. SEABED INTERVENTION

The following seabed intervention was undertaken:

- **Boulder Removal:** Removal of boulders on the seabed within the pipelay corridor.
- **Pre-Lay Dredging:** Pre-lay dredging of approximately twenty-four (24) kilometres of the pipelay route in Faxe Bugt and approximately four (4) kilometres of the pipelay route off Bornholm Island.
- **Concrete Mattress Installation:** Installation of concrete mattresses at various pipeline and cable crossing locations.
- **Pre-Lay Rock Installation:** Pre-lay rock installation at crossing and span support locations.
- **Post-Lay Rock Installation:** Post-lay rock installation in vicinity of micro-tunnel exit and at various crossing, span support and stability berm locations.
- **Post-Lay Backfilling:** Post-lay backfilling (including localised rectification work) of all dredged areas after pipelay and post-lay rock installation.

A detailed list of all seabed intervention locations in Danish waters is provided in Table 4-4. Boulder removal locations have not been considered due to the localised nature of the work undertaken.

Table 3-2: List of Seabed Intervention Locations

| KP | | Seabed Intervention | | | | |
|---------|---------|---------------------|---------------------|---------------------------|----------------------------|----------------------|
| Start | End | Pre-Lay Dredging | Concrete Mattresses | Pre-Lay Rock Installation | Post-Lay Rock Installation | Post-Lay Backfilling |
| 0.951 | 25.030 | Y ⁽¹⁾ | - | - | Y ⁽²⁾ | Y |
| 26.781 | 26.801 | - | - | - | Y | - |
| 27.000 | 27.300 | - | - | - | Y | - |
| 29.747 | 30.250 | - | Y ⁽³⁾ | - | Y | - |
| 32.325 | 32.625 | - | - | - | Y | - |
| 140.972 | 141.022 | - | Y ⁽³⁾ | - | Y | - |
| 164.026 | 164.036 | - | - | - | Y | - |
| 164.071 | 164.081 | - | - | - | Y | - |
| 164.891 | 164.901 | - | - | - | Y | - |
| 164.928 | 164.938 | - | - | - | Y | - |
| 165.130 | 165.150 | - | - | - | Y | - |
| 166.102 | 166.112 | - | - | - | Y | - |
| 167.015 | 167.025 | - | - | - | Y | - |
| 167.042 | 167.070 | - | - | - | Y | - |
| 167.400 | 171.500 | - | - | - | Y | - |
| 173.825 | 178.302 | Y ⁽¹⁾ | - | - | - | Y |
| 178.307 | 178.390 | - | - | Y ⁽³⁾ | Y | - |
| 180.759 | 180.809 | - | Y ⁽³⁾ | - | Y | - |
| 188.524 | 188.678 | - | Y ⁽³⁾ | Y ⁽³⁾ | Y | - |
| 188.735 | 188.865 | - | Y ⁽³⁾ | Y ⁽³⁾ | Y | - |
| 206.064 | 206.298 | - | Y ⁽³⁾ | Y ⁽³⁾ | Y | - |

Notes:

- (1) The spoil storage philosophy adopted during performance of the pre-lay dredging scope is described in Section 3.2.1.
- (2) Post-lay rock installation was undertaken within part of the reported KP range prior to undertaking post-lay backfilling. The extent of post-lay backfilling encompasses the areas of post-lay rock installation.
- (3) Concrete mattresses and /or pre-lay rock installation was undertaken within part of the reported KP range prior to pipeline installation. The extent of post-lay rock installation encompasses the pre-lay seabed intervention works.

3.2.1. Spoil Storage Philosophy

The philosophy adopted for the temporary storage of the dredged material varied for each location based on a range of factors including environmental restrictions, the extents of the permitted construction corridor and vessel specific minimum water depth requirements. The approach taken in Danish waters is summarised below.

The excavated material produced from the dredging operations was stored in the following manner:

- **Dredging at TBM Exit Pit ^[1]:** Excavated material was stored in the temporary spoil storage areas at KP1.660 and KP13.000.
- **Dredging of Pipeline Trench in Water Depth >7m:** Excavated material was side cast (i.e. deposited) alongside the pipeline trench. The spoil heaps were located within the +/- 125m construction corridor – offset no greater than 20m from the route centreline.
- **Dredging of Pipeline Trench in Water Depths <7m ^[2]:** Excavated material was stored at the aforementioned temporary spoil storage areas at KP1.660 and KP13.000.

Notes:

- (1) The “Environmental Impact Assessment – Denmark – Baltic Sea” [Ref. /2/] specified that spoil excavated from the exit pit and trench transition must be stored in water depths greater than 7m to avoid covering the eel grass meadow in the vicinity of the exit pit.
- (2) The “Environmental Impact Assessment – Denmark – Baltic Sea” [Ref. /2/] specified that trench spoil could only be side cast in water depths greater than 7m whether related to the exit pit, trench transition or any other trenching operations.

The boundary co-ordinates of the temporary spoil storage areas at KP1.660 and KP13.000 are detailed in Table 3-3 and Table 3-4 respectively. Both storages areas were located within the UXO surveyed zone extending up to +/-1000m from the pipeline route centreline.

Table 3-3: Boundary Co-ordinates - Temporary Spoil Storage Area at KP1.660

| ID | WGS 84 | | UTM 33N | |
|----|----------------|----------------|------------|--------------|
| | Latitude – N | Longitude – E | Easting | Northing |
| 1 | 55° 10' 45.91" | 12° 08' 51.77" | 318 384.68 | 6 118 469.94 |
| 2 | 55° 10' 49.10" | 12° 08' 52.74" | 318 405.80 | 6 118 567.69 |
| 3 | 55° 10' 51.86" | 12° 08' 24.90" | 317 917.07 | 6 118 673.28 |
| 4 | 55° 10' 48.68" | 12° 08' 23.93" | 317 895.95 | 6 118 575.54 |

Table 3-4: Boundary Co-ordinates - Temporary Spoil Storage Area at KP13.000

| ID | WGS 84 | | UTM 33N | |
|----|----------------|----------------|------------|--------------|
| | Latitude – N | Longitude – E | Easting | Northing |
| 5 | 55° 09' 35.96" | 12° 18' 50.22" | 328 883.53 | 6 115 888.22 |
| 6 | 55° 09' 32.76" | 12° 18' 49.42" | 328 865.58 | 6 115 789.84 |
| 7 | 55° 09' 33.67" | 12° 19' 18.18" | 329 375.41 | 6 115 798.45 |
| 8 | 55° 09' 30.47" | 12° 19' 17.38" | 329 357.46 | 6 115 700.08 |

3.3. PIPELINE CONFIGURATION ALONG ROUTE

The configuration of the pipeline along the route, which is determined giving consideration to the seabed intervention activities described in Section 3.2, is summarised in Table 3-5.

Table 3-5: Pipeline Configuration Along Route

| KP | | Pipeline Configuration | | |
|---------|---------|------------------------|-------------|-------------------|
| Start | End | Trenched & Buried | Rock Dumped | Exposed on Seabed |
| 0.951 | 25.030 | Y | - | - |
| 25.030 | 26.781 | - | - | Y |
| 26.781 | 26.801 | - | Y | - |
| 26.801 | 27.000 | - | - | Y |
| 27.000 | 27.300 | - | Y | - |
| 27.300 | 29.747 | - | - | Y |
| 29.747 | 30.250 | - | Y | - |
| 30.250 | 32.325 | - | - | Y |
| 32.325 | 32.625 | - | Y | - |
| 32.625 | 47.111 | - | - | Y |
| 132.102 | 140.972 | - | - | Y |
| 140.972 | 141.022 | - | Y | - |
| 141.022 | 164.026 | - | - | Y |
| 164.026 | 164.036 | - | Y | - |
| 164.036 | 164.071 | - | - | Y |
| 164.071 | 164.081 | - | Y | - |
| 164.081 | 164.891 | - | - | Y |
| 164.891 | 164.901 | - | Y | - |
| 164.901 | 164.928 | - | - | Y |
| 164.928 | 164.938 | - | Y | - |
| 164.938 | 165.130 | - | - | Y |
| 165.130 | 165.150 | - | Y | - |
| 165.150 | 166.102 | - | - | Y |
| 166.102 | 166.112 | - | Y | - |
| 166.112 | 167.015 | - | - | Y |
| 167.015 | 167.025 | - | Y | - |
| 167.025 | 167.042 | - | - | Y |
| 167.042 | 167.070 | - | Y | - |
| 167.070 | 167.400 | - | - | Y |
| 167.400 | 171.500 | - | Y | - |
| 171.500 | 174.000 | - | - | Y |
| 173.825 | 178.302 | Y | - | - |
| 178.200 | 178.307 | - | - | Y |
| 178.307 | 178.390 | - | Y | - |
| 178.390 | 180.759 | - | - | Y |
| 180.759 | 180.809 | - | Y | - |
| 180.809 | 188.524 | - | - | Y |
| 188.524 | 188.678 | - | Y | - |
| 188.678 | 188.735 | - | - | Y |
| 188.735 | 188.865 | - | Y | - |
| 188.865 | 206.064 | - | - | Y |
| 206.064 | 206.298 | - | Y | - |
| 206.298 | 217.806 | - | - | Y |

3.4. PIPELINE START-UP AND ANCHOR HANDLING OPERATIONS

Three (3) pipelay vessels were utilised to install the offshore pipeline in Danish territorial and EEZ waters. The actual pipelay vessel battery limits and pipelay direction (in Danish waters) are summarised in Table 3-6.

Table 3-6: Pipelay Vessel Battery Limits and Lay Direction (in Danish Waters)

| KP | | Pipelay Vessel | Pipelay Mode | Pipelay Direction |
|---------|---------------------|----------------|--------------|-------------------|
| From | To | | | |
| 0.000 | 19.500 | Castoro 10 | Moored | DK – PL |
| 19.500 | 41.980 ¹ | Castoro Sei | Moored | PL – DK |
| 41.980 | 47.111 | Castorone | DP | PL – DK |
| 132.102 | 150.700 | Castorone | DP | PL – DK |
| 150.700 | 182.000 | Castoro Sei | Moored | DK – PL |
| 182.000 | 217.806 | Castorone | DP | DK – PL |

The pipeline was initiated via a start-up anchor located at KP150.700.

Pipelay vessels “Castoro Sei” and “Castoro 10” installed their assigned sections of the pipeline in moored pipelay mode. The anchors were positioned up to +/-1000m or +/-750m each side of the planned pipeline centreline for “Castoro Sei” and “Castoro 10” respectively. Specific anchor patterns were prepared at crossing locations and where confirmed or potential cultural heritage objects were identified.

Minor and localised physical disturbances of the seabed would have occurred at locations where the start-up anchor and vessel mooring anchors were placed, and where the anchor lines interacted with the seabed. It has not been feasible to consider the impact of the pipeline start-up anchor or pipelay vessel anchor handling operations within this assessment. However, the “*Environmental Impact Assessment – Baltic Sea – Denmark*” [Ref. /2/] concludes that:

“The impact from [...] anchors is assessed to be local and does not impact the general bathymetry of the Baltic Sea.”

4. ENVIRONMENTAL REPORTING: PHYSICAL LOSSES AND PHYSICAL DISTURBANCES OF THE SEABED

4.1. SEABED TOPOGRAPHY

4.1.1. Methodology

The following methodology was used to assess the physical disturbances of the seabed, resulting from implementation of the Baltic Pipe Project, by considering changes in seabed topography.

Qualitative Description of Observed Changes in Seabed Topography at Locations of Seabed Intervention:

Physical losses and physical disturbances of the seabed primarily occur when seabed intervention works are undertaken.

The assessment is undertaken by providing a qualitative description of any observed changes in seabed topography at a selection of locations where seabed intervention has been undertaken. The locations are selected on the basis that they are representative of the different types and extents of seabed intervention work and the construction methodologies employed.

A detailed list of all seabed intervention locations in Danish waters is provided in Table 3-2. The following locations are selected for assessment.

Table 4-1: Selected Seabed Intervention Locations

| Location | KP | Seabed Intervention | | | | |
|----------|---------|------------------------------|---------------------|---------------------------|----------------------------|----------------------|
| | | Pre-Lay Dredging | Concrete Mattresses | Pre-Lay Rock Installation | Post-Lay Rock Installation | Post-Lay Backfilling |
| A1 | 1.010 | Y | - | - | Y | Y |
| A2 | 1.660 | Temporary Spoil Storage Area | | | | |
| A3 | 19.500 | Y | - | - | Y | Y |
| A4 | 29.800 | - | Y | - | Y | - |
| A5 | 167.050 | - | - | - | Y | - |
| A6 | 176.000 | Y | - | - | - | Y |
| A7 | 188.600 | - | Y | Y | Y | - |

At each of the selected locations, a cross sectional drawing is presented showing the seabed topography, obtained by multi-beam survey, prior to and following performance of the seabed intervention works. A description of any observed changes in seabed topography is provided along with an accompanying narrative of the seabed intervention works and the construction methodology employed.

Qualitative Description of Observed Changes in Seabed Topography at Locations Where Pipeline is Exposed on the Seabed:

The pipeline is exposed on the seabed at locations where seabed intervention has not been undertaken. Immediately after pipeline installation, the pipeline may have embed into the seabed due its self-weight. The magnitude of embedment along the pipeline route is linked to the seabed substrate type at the location concerned. The seabed topography will be permanently affected by the presence of the pipeline and the potential exists for the pipeline to act as a barrier to the flow of bottom currents. The long term impact on seabed topography is predicted to be insignificant and will only be known if further monitoring activities are undertaken in the future.

The assessment is undertaken by providing a qualitative description of any observed changes in seabed topography at a selection of locations where the pipeline is exposed on the seabed. The locations selected, which are representative of the four (4) seabed substrate types present along the pipeline route are identified in Table 4-2. Refer to Section 4.2.1 for an explanation of the classification system utilised.

Table 4-2: Selected Locations Where Pipeline is Exposed on the Seabed

| Location | KP | Seabed Substrate Type |
|----------|---------|-----------------------|
| B1 | 165.500 | Bedrock |
| B2 | 28.000 | Hard Bottom |
| B3 | 135.000 | Fine Grained Sediment |
| B4 | 181.000 | Sand |

It is understood that the soil conditions are likely to be variable within each seabed substrate type and the levels of embedment observed at other locations along the route may differ.

4.1.2. Assessment

The results of the assessment, considering the aforementioned methodology, are provided for each selected location below.

For each of the cross-sectional profiles:

- The horizontal distance along the cross section, in metres, is indicated on the x-axis. 0m denoted the design centreline of the pipeline.
- The water depth, in metres, is indicated on the y-axis. 0m denotes the mean water level.

Location A1: KP1.010

Location A1 is in the vicinity of the micro-tunnel exit pit. The micro-tunnel exit pit is the end point of the 1000m long micro-tunnel that was bored under the Danish coastline from the landfall site. The exit pit, which is approximately 105m wide, was excavated for the recovery of the tunnel boring machine (TBM). The overall width of the exit pit was largely governed by the side slope geometry – which was an important consideration for slope stability and diver safety during the TBM recovery operation.

Minimal disturbance of the seabed is observed each side of the trench because all excavated material was placed at two (2) temporary spoil storage areas – located in water depths greater than seven (7) metres. The use of temporary spoil storage areas was part of the measures employed to minimise disturbance of the eel grass meadows in the vicinity of the micro-tunnel exit pit.

A shore pull-in operation was undertaken to pull the offshore pipeline through the micro-tunnel to the landfall site. Following pipeline installation, the trench was partially filled with rock material using a side stone dumping vessel (SSDV). Backfilling of the previously excavated soil material was primarily undertaken using split hopper barges. The split hopper barges transported spoil recovered from the temporary spoil storage areas back to the exit pit location – where the material was returned to the trench. Localised rectification work was undertaken using backhoe dredgers and grab dredgers.

The cross-sectional profile illustrated in Figure 4-1 indicates very close alignment between the pre-dredging and post-backfilling seabed profiles. The pre-dredging seabed profile is indicated with a black line and the post-backfilled seabed profile is indicated with a red line.




Figure 4-1: Cross-Sectional Profile at KP1.010

Location A2: KP1.660

Location A2 is the location of one (1) of two (2) temporary spoil storage areas. The width of the spoil storage area was approximately 100m. Material excavated from the pipeline trench during pre-lay dredging, with specific water depth and environmental constraints preventing side casting, was placed within the temporary spoil storage areas using split hopper barges.

During post-lay backfilling operations, the material was recovered from the temporary spoil storage areas by backhoe dredgers and grab dredgers and placed into split hopper barges. The split hopper barges transported the material back to the pipeline for placement into the trench.

The cross sectional profile is illustrated in Figure 4-2. The as-found seabed profile is indicated with a black line and the as-left seabed profile is indicated with a red line. Review of the profiles indicate that some of the original seabed may have been excavated whilst recovering the previously dumped spoil for the post-lay backfilling operation. This is to be expected considering the capability and accuracy of the equipment employed. It is also observed that the seabed elevation at the edges of the spoil storage area recorded in the as-left survey are greater than those obtained in the as-found survey. It is worth highlighting that sediment transport arising from environmental actions (i.e. from waves and currents) was observed during the period between pre-lay dredging and post-lay backfilling. This is likely to have resulted in some material within the spoil storage area migrating outside its boundary.




Figure 4-2: Cross-Sectional Profile at KP1.660

Location A3: KP19.500

Location A3 is the location of the pipeline above water tie-in. Prior to pipeline installation, a trapezoid shaped trench, with maximum width of approximately 40m, was dredged. The excavated material was side cast adjacent to the trench. Initially the section of pipeline installed from Poland was laid down within the trench. At a later date, the section of pipeline installed from Denmark was laid down within the trench with an offset of approximately 4m. The pipeline above water tie-in operation involved the recovery of the two (2) pipeline sections, laid in opposite directions, onboard pipelay vessel "Castoro 10" where they were welded together. Following the tie-in operation, the pipeline was lowered to the seabed – the excess length being managed by laying the pipeline in an "Omega" shape.

Rock was installed on the pipeline at three (3) locations within the trapezoid shaped trench. During post-lay backfilling operations, the previously side cast material was returned to the trench in such a manner that the minimum backfill requirements were achieved.

The above water tie-in arrangement and approximate location of the cross sectional profile is indicated in Figure 4-3.




Figure 4-3: Above Water Tie-in Trench Configuration with Rock Installation Locations

The design cross-section at this location is indicated in Figure 4-4.




Figure 4-4: Configuration at Pipeline Above Water Tie-in

The cross sectional profile is illustrated in Figure 4-5. The pre-dredging seabed profile is indicated with a black line and the as-left seabed profile is indicated with a red line. Review of the profiles indicate that the as-left seabed elevation is greater than the pre-dredging elevation in the

vicinity of the pipeline centre-line (0m on the horizontal axis) – in accordance with the design requirements. The as-left seabed elevation is marginally lower than the pre-dredging elevation across approximately 45m of the cross section (-52m to -7m on the horizontal axis).




Figure 4-5: Cross Sectional Profile at KP19.500

Location A4: KP29.800

Location A4 is in the vicinity of the location where the Baltic Pipe offshore pipeline crosses the Kriegers Flak cable. The crossing arrangement and approximate location of the cross sectional profile is indicated in Figure 4-6.




Figure 4-6: Kriegers Flak Cable Crossing

Prior to pipeline installation, concrete mattresses and a pre-lay rock carpet were installed over the existing asset – which is trenched and buried at this location. The rock was installed using a dynamically positioned fall pipe vessel (DPFPV).

The concrete mattresses and rock carpet provide protection to the cable during pipeline installation and operation. Following installation of the pipeline, post-lay rock installation was undertaken using DPFPV. The rock encompasses the concrete mattresses and pipeline at this location.

The cross sectional profile is illustrated in Figure 4-7. The as-found seabed profile is indicated with a black line and the post-rock installation seabed profile is indicated with a red line. It can be observed that the rock berm, which extends each side of the pipeline centreline (0m on horizontal axis), is approximately 16m in width and rises approximately 2.5m above the original seabed elevation.

The existing trenched and buried cable, converging towards the crossing location, is indicated by the "U" shaped configuration (-22m to -8m on the horizontal axis).




Figure 4-7: Cross Sectional profile at KP29.800

Location A5: KP167.050

Location A5 is a location where post-lay rock installation was undertaken for pipeline freespan support. The pipeline was initially installed on the natural seabed by pipelay vessel "Castoro Sei". During performance of on-bottom roughness analysis with the as-laid survey data, it was determined that spot rock installation was required for freespan support. Rock installation was undertaken using a DPFPPV.

The cross sectional profile is illustrated in Figure 4-8. The as-found seabed profile is indicated with a black line and the post-rock installation seabed profile is indicated with a red line. It can be observed that the rock berm, which extends each side of the pipeline centreline (0m on horizontal axis), is approximately 25m in width and rises approximately 2m above the original seabed elevation.




Figure 4-8: Cross Sectional Profile at KP167.050

Location A6: KP176.000

Location A6 is located south-west of Bornholm Island where the pipeline is installed within a trench. The trench was constructed prior to pipeline installation using primarily grab dredgers. The excavated material was side cast adjacent to the trench on the eastern side. Pipelay vessel "Castoro Sei" installed the pipeline within the trench.

During post-lay backfilling operations, the previously side cast material was returned to the trench using grab dredgers in such a manner that the minimum backfill requirements were achieved. The design configuration at this location is indicated in Figure 4-9.




Figure 4-9: Trench Design

The cross sectional profile is illustrated in Figure 4-10. The pre-dredging seabed profile is indicated with a black line and the post-backfill seabed profile is indicated with a red line. Review of the profiles indicate that the post-backfill seabed elevation is marginally lower than the pre-dredging elevation at the location of the pipeline trench (-8m to 7m on the horizontal axis). The post-backfill seabed elevation is marginally higher than the pre-dredging elevation at the location of the spoil heap (-31m to -8m on the horizontal axis).




Figure 4-10: Cross Sectional Profile at KP176.000

Location A7: KP188.600

Location A4 is in the vicinity of the location where the Baltic Pipe offshore pipeline crosses the Nord Stream 1A pipeline. The crossing arrangement and approximate location of the cross sectional profile is indicated in Figure 4-11.




Figure 4-11: Nord Stream 1A Pipeline Crossing

The design cross-section is indicated in Figure 4-12.




Figure 4-12: Nord Stream 1A Crossing Design

Prior to pipeline installation, concrete mattresses and a pre-lay rock carpet were installed over the Nord Stream 1A pipeline. The rock was installed using a dynamically positioned fall pipe vessel (DPFPV). The concrete mattresses and rock carpet provide protection to the pipelines during pipeline installation and operation. Following installation of the pipeline, post-lay rock installation was undertaken using DPFPV. The rock encompasses the concrete mattresses and both pipelines at this location.

The cross sectional profile is illustrated in Figure 4-13. The as-found seabed profile is indicated with a black line and the post-rock installation seabed profile is indicated with a red line. It can be observed that the rock berm, which extends each side of the pipeline centreline (0m on horizontal axis), is approximately 70m in width and rises approximately 3.5m above the natural seabed elevation at its highest point.




Figure 4-13: Cross Sectional Profile at KP188.600

Location B1 – B4: Pipeline Exposed on Seabed

The pipeline configuration on the seabed at Locations B1 to B4 are presented in Figure 4-14. The magnitude of pipeline embedment at each location reflects the soil parameters at the location concerned.

No embedment is observed at the selected locations with Bedrock (Location B1) and Hard Bottom (Location B2) seabed substrate types.

Minimal embedment is observed at the selected location with Sand (Location B4) seabed substrate type.

The pipeline is embedded to approximately half its diameter at the selected location with Fine Grained Sediment (Location B3) seabed substrate type.

It is understood that the soil conditions are likely to be variable within each seabed substrate type and the levels of embedment at other locations along the route may differ.







Figure 4-14: Cross-Sectional Profiles at Locations B1 – B4

4.2. SEABED HABITAT TYPE

4.2.1. Methodology

The following methodology was used to assess the physical losses and physical disturbances of the seabed, with respect to seabed habitat type, resulting from implementation of the Baltic Pipe Project.

Overlay of Benthic Habitat Types on Pipeline Route Layout:

For the entire Baltic Sea region, sixty (60) different benthic habitat types have been identified – each of these habitat types reflect its specific combination of basic physical properties, i.e. substrate type, light availability and salinity.

The benthic habitat types defined in the “*Environmental Impact Assessment – Baltic Sea – Denmark*” [Ref. /2/], which originate from the BALANCE Project (<https://balance-eu.org/>) and the Danish marine substrate classification system, have been considered in this assessment.

The BALANCE Project data was downloaded, as GeoTiff files, from the HELCOM Map and Data Service (<https://maps.helcom.fi/website/mapservice/index.html>) and overlaid onto the route layout map.

The boundaries of each benthic habitat type were determined, in kilometre post (KP) notation, from the pipeline route layout map. In Danish waters, the pipeline crosses and therefore potentially impacts ten (10) benthic habitat types which are represented by four (4) substrate types. The benthic habitat types and their locations along the pipeline route are indicated in Table 4-3 and Table 4-4 respectively.

Table 4-3: Benthic Habitat Types Crossed by Pipeline Route

| Substrate Type | Photic / Non-Photic Zone | Salinity (PSU) |
|-----------------------|--------------------------|----------------|
| Bedrock | Non-Photic | 7.5 – 11 |
| Hard Bottom | Non-Photic | 7.5 – 11 |
| Hard Bottom | Non-Photic | 11 – 18 |
| Hard Bottom | Photic | 11 – 18 |
| Fine Grained Sediment | Non-Photic | 7.5 – 11 |
| Fine Grained Sediment | Non-Photic | 11 – 18 |
| Fine Grained Sediment | Photic | 11 – 18 |
| Sand | Non-Photic | 7.5 – 11 |
| Sand | Non-Photic | 11 – 18 |
| Sand | Photic | 11 – 18 |

Table 4-4: Location of Benthic Habitat Types Along Pipeline Route

| KP | | Substrate Type | Photic / Non-Photic Zone | Salinity (PSU) |
|---------|---------|-----------------------|--------------------------|----------------|
| Start | End | | | |
| 0.951 | 1.174 | Fine Grained Sediment | Photic | 11 – 18 |
| 1.174 | 2.132 | Hard Bottom | Photic | 11 – 18 |
| 2.132 | 3.028 | Fine Grained Sediment | Photic | 11 – 18 |
| 3.028 | 3.979 | Sand | Photic | 11 – 18 |
| 3.979 | 9.494 | Hard Bottom | Photic | 11 – 18 |
| 9.494 | 10.930 | Sand | Photic | 11 – 18 |
| 10.930 | 11.135 | Sand | Non-Photic | 11 – 18 |
| 11.135 | 12.156 | Hard Bottom | Non-Photic | 11 – 18 |
| 12.156 | 18.429 | Sand | Photic | 11 – 18 |
| 18.429 | 21.048 | Sand | Non-Photic | 11 – 18 |
| 21.048 | 25.073 | Hard Bottom | Non-Photic | 11 – 18 |
| 25.073 | 29.290 | Hard Bottom | Photic | 11 – 18 |
| 29.290 | 29.692 | Fine Grained Sediment | Photic | 11 – 18 |
| 29.692 | 32.308 | Fine Grained Sediment | Non-Photic | 11 – 18 |
| 32.308 | 37.338 | Hard Bottom | Non-Photic | 11 – 18 |
| 37.338 | 47.111 | Fine Grained Sediment | Non-Photic | 11 – 18 |
| 132.102 | 148.741 | Fine Grained Sediment | Non-Photic | 11 – 18 |
| 148.741 | 155.129 | Fine Grained Sediment | Non-Photic | 7.5 – 11 |
| 155.129 | 165.068 | Sand | Non-Photic | 7.5 – 11 |
| 165.068 | 165.936 | Bedrock | Non-Photic | 7.5 – 11 |
| 165.936 | 166.958 | Hard Bottom | Non-Photic | 7.5 – 11 |
| 166.958 | 182.758 | Sand | Non-Photic | 7.5 – 11 |
| 182.758 | 185.237 | Fine Grained Sediment | Non-Photic | 7.5 – 11 |
| 185.237 | 186.445 | Hard Bottom | Non-Photic | 7.5 – 11 |
| 186.445 | 217.806 | Fine Grained Sediment | Non-Photic | 7.5 – 11 |

Determine Extent of Physical Losses and Physical Disturbances of the Seabed:

The pipeline was split into a number of discrete sections based on the benthic habitat type, the type and extend of seabed intervention and the resulting pipeline configuration.

For each discrete section, the following process was followed:

1. The pipeline configuration was used to assess whether a physical loss or physical disturbance was observed within the discrete pipeline section concerned:

| Pipeline Configuration | Classification |
|------------------------|----------------------|
| Trench & Buried | Physical Disturbance |
| Rock Dumped | Physical Loss |
| Exposed on Seabed | Physical Loss |

2. Where the pipeline is trenched and buried, the "footprint" of the physical disturbance was determined from the corresponding post-backfill survey chart:

| Document Title | Ref. |
|--|------------|
| Rohde Nielsen – Post Backfill Survey Charts (Denmark) – Area 1 | [Ref. /5/] |
| Rohde Nielsen – Post Backfill Survey Charts (Denmark) – Area 2 | [Ref. /6/] |
| Rohde Nielsen – Post Backfill Survey Charts (Denmark) – Area 3 | [Ref. /7/] |

3. Where the pipeline is rock dumped, the "footprint" of the physical loss was determined from the corresponding as-built drawing:

| Document Title | Ref. |
|---|-------------|
| DEME – As-Built Drawing Danish Landfall Rock Placement | [Ref. /8/] |
| DEME – As-Built Drawing Lock Berm KP26.781 – Post-Lay | [Ref. /9/] |
| DEME – As-Built Drawing Lock Berm KP27.000 – Post-Lay | [Ref. /10/] |
| DEME – As-Built Drawing Kriegers Flak EC Crossing – Post-Lay | [Ref. /11/] |
| DEME – As-Built Drawing Lock Berm KP32.325 – Post-Lay | [Ref. /12/] |
| DEME – As-Built Drawing C-Lion Crossing – Post-Lay | [Ref. /13/] |
| DEME – As-Built Drawing Span Support KP164.026 – KP164.036 | [Ref. /14/] |
| DEME – As-Built Drawing Span Support KP164.071 – KP164.081 | [Ref. /15/] |
| DEME – As-Built Drawing Span Support KP164.891 – KP164.901 | [Ref. /16/] |
| DEME – As-Built Drawing Span Support KP164.928 – KP164.938 | [Ref. /17/] |
| DEME – As-Built Drawing Span Support KP165.130 – KP165.150 | [Ref. /18/] |
| DEME – As-Built Drawing Span Support KP166.102 – KP166.112 | [Ref. /19/] |
| DEME – As-Built Drawing Span Support KP167.015 – KP167.025 | [Ref. /20/] |
| DEME – As-Built Drawing Span Support KP167.042 – KP167.070 | [Ref. /21/] |
| DEME – As-Built Drawing – Post-Lay Rock Placement – Ronne Bank Stability Berm | [Ref. /22/] |
| DEME – As-Built Drawing Span Support KP178.333 – Post-Lay | [Ref. /23/] |
| DEME – As-Built Drawing Baltica Segment 3 Crossing – Post-Lay | [Ref. /24/] |
| DEME – As-Built Drawing Nord Stream 1A Crossing – Post-Lay | [Ref. /25/] |
| DEME – As-Built Drawing Nord Stream 1B Crossing – Post-Lay | [Ref. /26/] |
| DEME – As-Built Drawing Nord Stream 2 Crossing – Post-Lay | [Ref. /27/] |

-
4. Where the pipeline is exposed on the seabed, the “footprint” of the physical loss was determined by multiplying the maximum concrete weight coated diameter of the pipeline by the length of the discrete pipeline section concerned.

The total extent of physical losses and physical disturbances for each impacted seabed habitat type along the pipeline route is calculated by summing the footprints determined in each discrete pipeline section.

4.2.2. Assessment

The “footprint” or extent of physical losses and physical disturbances of the seabed for each discrete pipeline section are reported in Table 4-5.

Table 4-5: Assessment of Physical Losses and Physical Disturbances of the Seabed

| KP | | Benthic Habitat Type | | | Seabed Intervention | | | | | Pipeline Configuration | | | Extent | | Reference |
|---------|---------|-----------------------|--------------------------|----------|---------------------|-------------------|---------------------------|----------------------------|----------------------|------------------------|-------------|-------------------|----------------------|-----------------------|-------------|
| Start | End | Substrate Type | Photic / Non-Photic Zone | Salinity | Pre-Lay Dredging | Concrete Mattress | Pre-Lay Rock Installation | Post-Lay Rock Installation | Post-Lay Backfilling | Trenched & Buried | Rock Dumped | Exposed on Seabed | Physical Loss | Physical Disturbance | |
| 0.951 | 1.174 | Fine Grained Sediment | Photic | 11 - 18 | Y | - | - | Y ⁽¹⁾ | Y | Y | - | - | | 19083 m ² | [Ref. /5/] |
| 1.174 | 2.132 | Hard Bottom | Photic | 11 - 18 | Y | - | - | Y ⁽¹⁾ | Y | Y | - | - | | 25468 m ² | |
| 2.132 | 3.028 | Fine Grained Sediment | Photic | 11 - 18 | Y | - | - | - | Y | Y | - | - | | 19556 m ² | |
| 3.028 | 3.979 | Sand | Photic | 11 - 18 | Y | - | - | - | Y | Y | - | - | | 19670 m ² | |
| 3.979 | 9.494 | Hard Bottom | Photic | 11 - 18 | Y | - | - | - | Y | Y | - | - | | 97700 m ² | |
| 9.494 | 10.930 | Sand | Photic | 11 - 18 | Y | - | - | - | Y | Y | - | - | | 22883 m ² | |
| 10.930 | 11.135 | Sand | Non-Photic | 11 - 18 | Y | - | - | - | Y | Y | - | - | | 3382 m ² | |
| 11.135 | 12.156 | Hard Bottom | Non-Photic | 11 - 18 | Y | - | - | - | Y | Y | - | - | | 14115 m ² | |
| 12.156 | 18.429 | Sand | Photic | 11 - 18 | Y | - | - | - | Y | Y | - | - | | 115288 m ² | |
| 18.429 | 21.048 | Sand | Non-Photic | 11 - 18 | Y | - | - | Y ⁽¹⁾ | Y | Y | - | - | | 57296 m ² | |
| 21.048 | 25.030 | Hard Bottom | Non-Photic | 11 - 18 | Y | - | - | - | Y | Y | - | - | | 64200 m ² | [Ref. /6/] |
| 25.030 | 25.073 | Hard Bottom | Non-Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 49 m ² | | - |
| 25.073 | 26.781 | Hard Bottom | Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 1964 m ² | | - |
| 26.781 | 26.801 | Hard Bottom | Photic | 11 - 18 | - | - | - | Y | - | - | Y | - | 159 m ² | | [Ref. /9/] |
| 26.801 | 27.000 | Hard Bottom | Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 229 m ² | | - |
| 27.000 | 27.300 | Hard Bottom | Photic | 11 - 18 | - | - | - | Y | - | - | Y | - | 4300 m ² | | [Ref. /10/] |
| 27.300 | 29.290 | Hard Bottom | Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 2289 m ² | | - |
| 29.290 | 29.692 | Fine Grained Sediment | Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 462 m ² | | - |
| 29.692 | 29.747 | Fine Grained Sediment | Non-Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 63 m ² | | - |
| 29.747 | 30.250 | Fine Grained Sediment | Non-Photic | 11 - 18 | - | Y ⁽²⁾ | - | Y | - | - | Y | - | 7681 m ² | | [Ref. /11/] |
| 30.250 | 32.308 | Fine Grained Sediment | Non-Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 2367 m ² | | - |
| 32.308 | 32.325 | Hard Bottom | Non-Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 20 m ² | | - |
| 32.325 | 32.625 | Hard Bottom | Non-Photic | 11 - 18 | - | - | - | Y | - | - | Y | - | 4386 m ² | | [Ref. /12/] |
| 32.625 | 37.338 | Hard Bottom | Non-Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 5420 m ² | | - |
| 37.338 | 47.111 | Fine Grained Sediment | Non-Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 11239 m ² | | - |
| 132.102 | 140.972 | Fine Grained Sediment | Non-Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 10201 m ² | | - |
| 140.972 | 141.022 | Fine Grained Sediment | Non-Photic | 11 - 18 | - | Y ⁽²⁾ | - | Y | - | - | Y | - | 571 m ² | | [Ref. /13/] |
| 141.022 | 148.741 | Fine Grained Sediment | Non-Photic | 11 - 18 | - | - | - | - | - | - | - | Y | 8877 m ² | | - |
| 148.741 | 155.129 | Fine Grained Sediment | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 7346 m ² | | - |
| 155.129 | 164.026 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 10232 m ² | | - |
| 164.026 | 164.036 | Sand | Non-Photic | 7.5 - 11 | - | - | - | Y | - | - | Y | - | 100 m ² | | [Ref. /14/] |
| 164.036 | 164.071 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 40 m ² | | - |
| 164.071 | 164.081 | Sand | Non-Photic | 7.5 - 11 | - | - | - | Y | - | - | Y | - | 88 m ² | | [Ref. /15/] |
| 164.081 | 164.891 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 932 m ² | | - |
| 164.891 | 164.901 | Sand | Non-Photic | 7.5 - 11 | - | - | - | Y | - | - | Y | - | 106 m ² | | [Ref. /16/] |
| 164.901 | 164.928 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 31 m ² | | - |
| 164.928 | 164.938 | Sand | Non-Photic | 7.5 - 11 | - | - | - | Y | - | - | Y | - | 86 m ² | | [Ref. /17/] |
| 164.938 | 165.068 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 150 m ² | | - |
| 165.068 | 165.130 | Bedrock | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 71 m ² | | - |
| 165.130 | 165.150 | Bedrock | Non-Photic | 7.5 - 11 | - | - | - | Y | - | - | Y | - | 139 m ² | | [Ref. /18/] |
| 165.150 | 165.936 | Bedrock | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 904 m ² | | - |
| 165.936 | 166.102 | Hard Bottom | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 191 m ² | | - |
| 166.102 | 166.112 | Hard Bottom | Non-Photic | 7.5 - 11 | - | - | - | Y | - | - | Y | - | 162 m ² | | [Ref. /19/] |
| 166.112 | 166.958 | Hard Bottom | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 973 m ² | | - |
| 166.958 | 167.015 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 66 m ² | | - |
| 167.015 | 167.025 | Sand | Non-Photic | 7.5 - 11 | - | - | - | Y | - | - | Y | - | 375 m ² | | [Ref. /20/] |

| KP | | Benthic Habitat Type | | | Seabed Intervention | | | | | Pipeline Configuration | | | Extent | | |
|---------|---------|-----------------------|--------------------------|----------|---------------------------------|-------------------|---------------------------|----------------------------|----------------------|------------------------|-------------|-------------------|----------------------|----------------------|-------------|
| Start | End | Substrate Type | Photic / Non-Photic Zone | Salinity | Pre-Lay Dredging | Concrete Mattress | Pre-Lay Rock Installation | Post-Lay Rock Installation | Post-Lay Backfilling | Trenched & Buried | Rock Dumped | Exposed on Seabed | Physical Loss | Physical Disturbance | Reference |
| 167.025 | 167.042 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 20 m ² | | - |
| 167.042 | 167.070 | Sand | Non-Photic | 7.5 - 11 | - | - | - | Y | - | - | Y | - | 791 m ² | | [Ref. /21/] |
| 167.070 | 167.400 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 380 m ² | | - |
| 167.400 | 171.500 | Sand | Non-Photic | 7.5 - 11 | - | - | - | Y | - | - | Y | - | 50842 m ² | | [Ref. /22/] |
| 171.500 | 173.825 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 2674 m ² | | - |
| 173.825 | 178.302 | Sand | Non-Photic | 7.5 - 11 | Y | - | - | - | Y | Y | - | - | | 86655 m ² | [Ref. /6/] |
| 178.302 | 178.307 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 6 m ² | | - |
| 178.307 | 178.390 | Sand | Non-Photic | 7.5 - 11 | - | - | Y (2) | Y | - | - | Y | - | 1404 m ² | | [Ref. /23/] |
| 178.390 | 180.759 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 2724 m ² | | - |
| 180.759 | 180.809 | Sand | Non-Photic | 7.5 - 11 | - | Y (2) | - | Y | - | - | Y | - | 536 m ² | | [Ref. /24/] |
| 180.809 | 182.758 | Sand | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 2241 m ² | | - |
| 182.758 | 185.237 | Fine Grained Sediment | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 2851 m ² | | - |
| 185.237 | 186.445 | Hard Bottom | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 1389 m ² | | - |
| 186.445 | 188.524 | Fine Grained Sediment | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 2391 m ² | | - |
| 188.524 | 188.678 | Fine Grained Sediment | Non-Photic | 7.5 - 11 | - | Y (2) | Y (2) | Y | - | - | Y | - | 7674 m ² | | [Ref. /25/] |
| 188.678 | 188.735 | Fine Grained Sediment | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 66 m ² | | - |
| 188.735 | 188.865 | Fine Grained Sediment | Non-Photic | 7.5 - 11 | - | Y (2) | Y (2) | Y | - | - | Y | - | 6017 m ² | | [Ref. /26/] |
| 188.865 | 206.064 | Fine Grained Sediment | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 19779 m ² | | - |
| 206.064 | 206.298 | Fine Grained Sediment | Non-Photic | 7.5 - 11 | - | Y (2) | Y (2) | Y | - | - | Y | - | 35840 m ² | | [Ref. /27/] |
| 206.298 | 217.806 | Fine Grained Sediment | Non-Photic | 7.5 - 11 | - | - | - | - | - | - | - | Y | 13234 m ² | | - |
| 1.660 | - | Hard Bottom | Photic | 11 - 18 | Temporary Spoil Storage Area #1 | | | | | | | | | 32670 m ² | [Ref. /5/] |
| 13.000 | - | Sand | Photic | 11 - 18 | Temporary Spoil Storage Area #2 | | | | | | | | | 46153 m ² | |

Notes:

- (1) Post-lay rock installation was undertaken within part of the reported KP range prior to undertaking post-lay backfilling. The extent of post-lay backfilling encompasses the areas of post-lay rock installation.
- (2) Concrete mattresses and /or pre-lay rock installation was undertaken within part of the reported KP range prior to pipeline installation. The extent of post-lay rock installation encompasses the pre-lay seabed intervention works.

A summary of results per benthic habitat type is presented in Table 4-6.

Table 4-6: Physical Losses and Physical Disturbances of the Seabed

| Benthic Habitat Type | | | Extent | |
|-----------------------|--------------------------|----------------|-----------------------------|-----------------------------|
| Substrate Type | Photic / Non-Photic Zone | Salinity (PSU) | Physical Loss | Physical Disturbance |
| Bedrock | Non-Photic | 7.5 – 11 | 1114 m ² | - |
| Hard Bottom | Non-Photic | 7.5 – 11 | 2715 m ² | - |
| Hard Bottom | Non-Photic | 11 – 18 | 9875 m ² | 78315 m ² |
| Hard Bottom | Photic | 11 – 18 | 8941 m ² | 123168 m ² |
| Fine Grained Sediment | Non-Photic | 7.5 – 11 | 95198 m ² | - |
| Fine Grained Sediment | Non-Photic | 11 – 18 | 40999 m ² | - |
| Fine Grained Sediment | Photic | 11 – 18 | 462 m ² | 38639 m ² |
| Sand | Non-Photic | 7.5 – 11 | 73824 m ² | 86655 m ² |
| Sand | Non-Photic | 11 – 18 | - | 60678 m ² |
| Sand | Photic | 11 – 18 | - | 157841 m ² |
| Total | | | 233128 m² | 545296 m² |
| Grand Total | | | 778424 m² | |

The total combined extent of physical losses and physical disturbances of the seabed is assessed to be 778424 m². This comprises 233128 m² of physical losses and 545296 m² of physical disturbances.

4.3. COMPARISON WITH PREDICTIONS IN ENVIRONMENTAL IMPACT ASSESSMENT

The qualitative descriptions of observed changes in seabed topography at the selected locations demonstrate that the construction works have been undertaken in accordance with the design and using the methodologies considered in the “*Environmental Impact Assessment – Baltic Sea – Denmark*” [Ref. /2/].

Reference is also made to document “*Rohde Nielsen – Environmental Reporting: Restoration of the Seabed at Micro-Tunnel Exit – Denmark*” [Ref. /28/] which describes the steps that were taken during the performance of pre-lay dredging and post-lay backfilling in the vicinity of the micro-tunnel exit pit to minimise the impact on the eel grass meadows and ensure the restored seabed conditions create a habitat suitable for the re-establishment of eel grass.

Where the cross sectional profiles, at locations where the pipeline is trenched in water depths greater than seven (7) metres, indicate differences in seabed topography between the pre-dredging and post-backfilling condition the “*Environmental Impact Assessment – Baltic Sea – Denmark*” [Ref. /2/] states that:

“... the seabed height around the trench may vary from the surrounding seabed due to spoil heaps. However, artificial and natural backfilling will subsequently smoothen out the seabed bathymetry along the trenched pipeline sections.”

With regards to the extent of physical losses and physical disturbances of the seabed, the “*Environmental Impact Assessment – Baltic Sea – Denmark*” [Ref. /2/] predicted that:

“The physical loss and physical damage of the seabed during the construction phase along the Baltic Pipe route will be of a temporary nature and highly localised to the immediate footprint of the pipeline, which in Danish waters corresponds to a total occupied area of 0.15 km².”

The total area of physical losses and physical disturbances of the seabed, calculated according to the methodology presented in Section 4.2.1 and reported in Table 4-6, during project implementation was determined to be 778424m² (~0.78km²). This is several times larger than the prediction within the “*Environmental Impact Assessment – Baltic Sea – Denmark*” [Ref. /2/]. The areas cannot be directly compared due to approved design changes following preparation of the “*Environmental Impact Assessment – Baltic Sea – Denmark*” [Ref. /2/].

Areas of physical disturbances of the seabed, which make up more than two thirds of this area, can be attributed to the pre-lay dredging, spoil storage and post-lay backfilling activities. Dredging of the pipeline was undertaken at specific locations along the route to ensure stability of the pipeline and to provide protection from interaction with marine traffic. The “*Environmental Impact Assessment – Baltic Sea – Denmark*” [Ref. /2/] states that:

“... impacts from physical disturbance of the seabed will not result in changes in the benthic habitat type, and therefore the intensity of the impacts on benthic communities from the construction work is assessed to be medium and the impact is considered minor and not significant.”

Areas of physical losses of the seabed correspond to areas where the pipeline is either exposed on the seabed or rock dumped. The “*Environmental Impact Assessment – Baltic Sea – Denmark*” [Ref. /2/] states that:

“The pipeline presence may on the one hand result in a loss of infauna seabed habitat within the project footprint. On the other hand, the introduction of the pipeline may represent a new hard substrate (“artificial reef”) for sessile organisms and benthic macroalgae (within the photic zone).

Even though there will be a small negative impact from the pipeline due to the loss of soft seabed habitat, the introduced artificial reefs will change the existing habitats, with the potential for a minor degree of final positive impact. In conclusion, the impact of the presence of the pipeline on the local benthic communities is considered as not significant.”

The potential impacts on benthic habitats, flora and fauna resulting from construction activities and operation of the pipeline within Danish waters are considered to be non-significant and will not have any transboundary impact.